AWG | Data Sheet | Hollow jet pipes | Turbo-Spritze VSP 2235 Storz C



## **Turbo-Spritze VSP 2235 Storz** C

Art.-Nr. 10072803

The AWG Turbo-Nozzle with full jet look is designed to fight various type of fires. These nozzles can be used for internal as well as outside attack. The additional full jet lock (FJL for short) is the simplest way to prevent unintentional switching to the full jet. The intuitive operation (pull the beam tube head forward) is easy to handle without much training effort.

Date: 08.09.2024, subject to technical changes and errors.

AWG | Data Sheet | Hollow jet pipes | Turbo-Spritze VSP 2235 Storz C

## **Technical Data**

Inlet:	Storz 52 (C)
Inlet swivvelling:	Yes
Flow rate at reference pressure p1:	60 / 130 / 235
Reference pressure p1 [bar]:	6
Throw distance at reference pressure:	18-26-30 (Full jet), 7-15 (Spray jet)
max. permissible operating pressure [bar]:	16
Spray Angle [°]:	0-120
Handle:	Yes
Product colour:	black, red
Material Adapter:	Aluminium
Applicable Standard:	DIN EN 15182
Turbo Wheel:	ja
Nominal size:	2235
Full jet lock :	yes

Date: **08.09.2024**, subject to technical changes and errors.