Turbo-Spritze 2475 Export G2" AG

Art.-Nr. 69785260

The AWG Turbo-Nozzle 2475 is designed to fight various type of fires. These nozzles fulfil numerous national and international standards and can be used for internal as well as outside attack.

Date: **09.10.2026**, subject to technical changes and errors.

© AWG Fittings GmbH . Bergstraße 25 . D-89177 Ballendorf . awg-info@idexcorp.com . www.awg-fittings.com

Technical Data

Length [mm]:	265
Inlet:	BSP G 2" AG
Inlet swivvelling:	Yes
Reference pressure p1 [bar]:	6
max. permissible operating pressure [bar]:	16
Handle:	Yes
Material Adapter:	Aluminium
Applicable Standard:	DIN EN 15182
Turbo Wheel:	ja
Flow rate at reference pressure p1:	115 / 230 / 360 / 475
Spray Angle [°]:	0 - 160
Throw distance at reference pressure:	25-31-38-44 (Full jet), 10-19 (Spray jet)
Product colour:	black, yellow
Nominal size:	2475

Date: **09.10.2026**, subject to technical changes and errors.

© AWG Fittings GmbH . Bergstraße 25 . D-89177 Ballendorf . awg-info@idexcorp.com . www.awg-fittings.com