AWG | Data Sheet | Nozzles | HS-12 Strahlrohr Storz 38



## **HS-12 Strahlrohr Storz 38**

Art.-Nr. 60404497

© AWG Fittings GmbH . www.awg-fittings.com

The AWG HS jet pipes are characterized by their ease of use and robustness. By turning the switch head, you can switch continuously from shut-off to full jet to spray jet with a spray angle between 0° and 120°. The switch head is made of rubber and chrome-plated brass, the pipe section is made of extremely impact-resistant plastic.

Date: 08.09.2024, subject to technical changes and errors.

AWG | Data Sheet | Nozzles | HS-12 Strahlrohr Storz 38

## **Technical Data**

Length [mm]:	327
Width [mm]:	78
Height [mm]:	78
Weight [kg]:	1
Reference pressure p1 [bar]:	6
max. permissible operating pressure [bar]:	16
Applicable Standard:	DIN EN 15182
Handle:	No
Inlet:	Storz 38
Configuration:	HS 12
Product colour:	black, orange
Flow rate at reference pressure p1:	230 (Vollstrahl), 460 (Sprühstrah)
Throw distance at reference pressure:	28 (Full jet), 4,5 (spray jet)

Date: **08.09.2024**, subject to technical changes and errors.