



Art.-Nr. 31358034

ALCO APF 3 size monitors are true all-rounders. They show their strengths in the industrial and marine sector as well as in the firefighting sector. Depending on your requirements and design, these monitors are used in portable or fixed versions. A large selection of nozzles and accessories allows maximum flexibility in application. The APF 3-P is designed as a portable monitor for mobile use. The device equipped with nozzle or foam pipe is suitable for delivering water and any type of foam. The monitor resilient supporting legs have low-wear carbide stand tips and collapse for transport in just one action. Vertical adjustment is carried out via a self-locking spindle with hand wheel. Moreover, a built-in swivel range limit ensures stability at all times of use. The top and bottom sections of the monitor can be quickly and simply separated from each other without tools. On the one hand, this provides convenient handling combined with handles integrated in the top and bottom section. On the other hand, the modular design allows the use of the top section as a roof monitor by mounting it onto a suitable folding joint or roof flange. Furthermore, it can be operated using a single hose line thanks to the integrated collecting breeching with non-return valves at the monitor input. The listed basic model is without nozzle and input coupling. A corresponding coupling and nozzle configuration can be made in the listed accessories.

Technical Data

max. permissible operating pressure [bar]:	16
Material Adapter:	Aluminium, eloxiert
Outlet:	BSP G2½"AG
Inlet:	2x Storz 75 (B)
Sealing:	NBR
Flow rate at reference pressure p1:	4000
With base frame:	Yes
Angle horizontal [°]:	±120°
Angle vertical [°]:	+35° bis +90° (entriegelt -15° bis +90°)